

# AmCells

California, USA

## ASI 2025 Weighing Indicator

Material: ABS Plastic; Dimension: 250x160x150mm; Weight: 1.4kg



**Input signal range:** -19~+mV

**A/D conversion:** 20 bit Sigma-Delta analog to digital

**A/D sampling frequency:** 3.84kHz

**Load cell excitation voltage:** DC5V/150mA

**Display:** 6 digits 1.2 inches high, LED display

**Division number of the display:**  $\leq 100000d$

**Serial port:** Two RS232 interface

**Working temperature:** -10~+40°C

**Storage temperature:** -25~+55°C

**Relative humidity:**  $\leq 85\%$

**Power supply mode:** AC87~242V, electric current is 0.1; built-in DC6V/4.5Ah lead-acid battery

## PRODUCT FEATURES

- ◆ The functions of ordinary weighing and counting
- ◆ Two RS232 interface, with electrostatic protection, continuous output, MODBUS-RTU, can communicate with the host computer or external thermal printers or big screen display
- ◆ It can print the record format or duplicate format
- ◆ Manual/automatic counting and printing
- ◆ Transformer or power board supply optional
- ◆ RS485 interface with electrostatic protection (Optional)
- ◆ Bluetooth (Optional)
- ◆ Wall-Hanging/Rotating bracket (Optional)

